

# SMR 3215 TB T3

## Thru Beam

Photoelectric Sensors

**Compatible Transmitter:**

SMT 3000HC TB T3



Product Data	
Function	Receiver
Operation Mode	Thru Beam
Supply Voltage	10 - 30 V dc
Connection	3 pin, M8 plug
Sensing Range	15 m
Output	PNP
Output Status	N.C.
Housing Material	Nickel Plated Brass
Housing	M12 x 1

Technical Data	
Supply Voltage	10 - 30 V dc
Voltage Ripple	15 %
Reverse Polarity Protected	Yes
Short Circuit Protected	Yes
Current Consumption	Max. 8 mA
Max. Output Load	100 mA
Max. Residual Voltage	2,5 V
Max. Operation Frequency	> 40 Hz
Response Time ton / toff	< 13 ms / < 6 ms
Output Indicator	Yellow LED
Hysteresis	Approx. 30 %
Opening Angle	+/- 7°
Housing Material, Front Lens	Polycarbonate
Housing Material, Sensor Housing	Nickel Plated Brass
Cable	3 x 0,14 mm <sup>2</sup>
Cable Sleeve	PVC Ø 3,4 mm


**Environmental Data**

Vibration	10 - 55 Hz, 0,5 mm
Shock	30 g
Operation Temperature	-20 to +50 °C
Storage Temperature	-40 to +80 °C
Sealing Class	IP 67
Light Immunity 5°	35 000 lux

**Approvals**



**Wiring Diagram**




**Connections**

**3 pin, M8**


Sensor Plug (Male)




Cable Plug (Female)



Parallel Displacement



Angular Displacement



Dimensions

